

wire feeding units for MIG/MAG welding machines

- DVK 4 (standard)
wire feeding unit (horizontal design) high power
4-roller drive 140 W
 - DVK 3
wire feeding unit (vertical design) very light and handy
option: without wheels
 - DVG 1
wire feeding unit, light and handy specially for assembly work with robust safety frame for transport and protection of the feeder.
Wire spools from 5 kg up to 15 kg
 - DVK 4 / DVK 3 / DVG 1
euro-connection for the torch
rapid action coupling DN 5
control MS 15
- option:**
- control MSE 2 with single-knob operation and ampere-volt-meter (wire feed speed resp.)

DVK 4
DVK 3
DVG 1



technical data	DVK 4	DVK 3	DVG 1
wire feeder with 4-roller system	140 W / 42 V	100 W / 42 V	100 W / 42 V
wire speed	0,5 - 24 m/min.	0,5 - 24 m/min.	0,5 - 24 m/min.
diameter of wire	0,8 - 1,6 mm	0,8 - 1,6 mm	0,8 - 1,6 mm
dimensions L x W x H (mm)	630 x 320 x 290	560 x 240 x 510	640 x 280 x 270
wire spool up to	bis 300 mm	bis 300 mm	bis 300 mm
weight	25 kg	18,5 kg	12,5 kg

article number	DVK 4	DVK 3	DVG 1
gas-cooled	850.000.004	850.003.050	850.001.001
water-cooled	850.000.001	850.003.051	850.001.002